

SHOWER SHEDS PORTABLE BATHROOM UNIT

Structure:

External Dimensions: 2.4m(L) x 1.8m(W) x 2.7m(H)
Pre-primed, grooved Plyclad front wall
zincalume corrugate sides, rear & roof
Zincalume flashings and trim
Lockable doorway 2.0m(H) x 1.0m(W)
Frames with 70x45 H1.2 MSG8 timber, with H3.2 treated base plate
Lined with roofing paper to roof & builders wrap to walls
18mm H3.2 treated plywood flooring with 90x45mm H3 joists
100x100mm H5 Skids running 2.4m length of shed for strength when lifting/winchng
Ply wood used for internal walls-12mm/9mm
Walls are insulated & decorated

Internal:

NZ/AU products installed (toilet, mixers)
Shower size—900mm x 900mm x 2000mm(H)
Glass door & panels, framed in chrome aluminium
Coroma toilet with double flush (4/6lts)
Raymor shower/basin mixers & shower slider
Flooring is wood finish vinyl tile

Extras included:

Extractor fan, internal ceiling light, towel rail, mirror, vanity cabinet, shaver/tooth brush power point, external day/night adjustable sensor light, external plug point, external caravan power lead, 10m extension cable

How it works:

Required:

- A standard garden tap (if gas unit is used for hot water) or hot & cold water supply
- Access to 240v power
- Power point
- A near level surface
- Within 25 metres of a gully trap/inspection opening or other options are available

All waste travels to a macerating pump and discharges through a flexible hose direct to existing sewer, gully trap or similar point of discharge

Only toilet paper can be used in conjunction with the macerator as all other foreign objects will damage the motor resulting in a macerator replacement.

Macerator servicing can be arranged at an additional fee as it would need to be serviced on a regular basis, depending on usage

Optional extras:

Adjustable supports, gas unit for hot and cold water, Macerator—2 year warranty (regular servicing required), trailer mounted option